

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
1 September 2005 (01.09.2005)

PCT

(10) International Publication Number
WO 2005/080055 A1

(51) International Patent Classification⁷: **B28B 7/12**

(21) International Application Number:
PCT/KR2005/000458

(22) International Filing Date: 18 February 2005 (18.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10-2004-0011165
19 February 2004 (19.02.2004) KR

(71) Applicant and

(72) Inventor: **LEE, Jea-Sam** [KR/KR]; 547-1 Miju APT
3-503, Sungnae-dong, Kangnam-gu, Seoul 134-030 (KR).

(74) Agent: **JANG, Yu-Jin**; 5th F1, Eunseong Bldg., 601-18,
Yeoksam-dong, Kangnam-gu, Seoul 135-080 (KR).

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: APPARATUS AND METHOD FOR MANUFACTURING CERAMIC WARE

(57) Abstract: An apparatus and a method for manufacturing ceramic ware are disclosed. The apparatus has a pair of mold housings, each having a wire net formed in a housing frame so as to support a mold. An air ejection tube fixed to the wire net is formed of fibroid material so as to eject the air toward the inside of the mold. The apparatus further has support plates for fixedly supporting the mold housing, and hydraulic cylinders for driving the support plates. An air compressor provides the air to the air ejection tubes of the mold housings. The method includes preparing a lump of clay, cutting the clay into slab clays, inserting the slab clay into the mold housing, pressing and casting the slab clay into a desired clay piece, drying the clay piece, decorating the clay piece, and firing the clay piece.



WO 2005/080055 A1